

QUICKCAMP™

Climate-controlled shelter & pipe-handling system with all-weather fusion capability for pipe from 8" IPS to 36" OD (225mm to 900mm)

The QuickCamp™ works in conjunction with the MegaMc® PolyHorse® to increase productivity.

Patents Pending

OVERVIEW

The **QuickCamp™ System** is a lighted, insulated and climate-controlled enclosure that allows operators to fuse pipe day or night under all weather conditions. The QuickCamp System includes the QuickCamp Shelter housing an 824 or 1236 fusion carriage and the MegaMc® PolyHorse® and MegaMc Rollers productivity tools.

Two people can set up the QuickCamp Shelter from a 20' cargo container. The pipe is guided through the QuickCamp Shelter from the MegaMc PolyHorse by a remote-control operator. The carriage can be moved by 18" so that the pipe ends can be adjusted for proper face-off when pulling pipe through the shelter.

The QuickCamp System, which can also accommodate an 824/630 fusion machine carriage, fuses pipe from 8" IPS to 36" OD. The QuickCamp Shelter can be sold separately.

FEATURES

- Shelter folds into standard ISO, 20' cargo container for shipping
- Folded shelter contains fusion machine carriage
- Carriage slides out of shelter for in-ditch use or fusing stub ends and fittings
- Ample space for an office, breakroom or storage of extra gear
- Electrical outlets to power personal equipment
- Hydraulic Power Unit powers fusion carriage with customer-furnished generator
- One-size-fits-all pipe seals
- Included heating and air-conditioning units fit into fold-out shelves



Machine operator and fusion joints are protected from the elements inside the shelter.

SPECIFICATIONS

CAPACITY

Pipe Size Range:8" IPS to 36" OD (225mm to 900mm)

POWER

| PIPE SIZE RANGE | INCLUDED MACHINE | INPUT POWER | ELECTRICAL OUTLETS | PART NO. |
|-------------------------------------|------------------|-----------------|--------------------|----------|
| 8" IPS - 24" OD (225mm - 630mm) | 630 High Force | 208V, 60Hz, 3Ph | 120V, 60Hz | A3658701 |
| | 630 Medium Force | | | A3658702 |
| | 630 Low Force | | | A3658703 |
| | 630 High Force | 240V, 50Hz, 3Ph | 240V, 50Hz | A3658704 |
| | 630 Medium Force | | | A3658705 |
| | 630 Low Force | | | A3658706 |
| | 630 High Force | 415V, 50Hz, 3Ph | 240V, 50Hz | A3658707 |
| | 630 Medium Force | | | A3658708 |
| | 630 Low Force | | | A3658709 |
| 12" IPS - 36" OD (340mm - 900mm) | 900 High Force | 208V, 60Hz, 3Ph | 120V, 60Hz | A3658501 |
| | 900 Medium Force | | | A3658502 |
| | 900 Low Force | | | A3658503 |
| | 900 High Force | 240V, 50Hz, 3Ph | 240V, 50Hz | A3658504 |
| | 900 Medium Force | | | A3658505 |
| | 900 Low Force | | | A3658506 |
| | 900 High Force | 415V, 50Hz, 3Ph | 240V, 50Hz | A3658507 |
| | 900 Medium Force | | | A3658508 |
| | 900 Low Force | | | A3658509 |

*Shelter is available separately from package. A3659001: 208V/120V. A3659002: 240V/240V. A3659003: 415V/240V.

INCLUSIONS

The QuickCamp System includes the QuickCamp Shelter, three standard 20' dry freight containers, MegaMc® PolyHorse® and MegaMc® Rollers pipe handling systems, and two pipe support stands.

QUICKCAMP™

Climate-controlled shelter & pipe-handling system with all-weather fusion capability for pipe from 8" IPS to 36" OD (225mm to 900mm)



Patent-pending pipe enclosures keep the elements out and the operator and fusion area protected.



Fusion carriage can be removed for in-ditch use or fusing of stub ends and fittings.

DIMENSIONS AND LAYOUT

