



www.performancepipe.com

Product Submittal Sheet

Municipal, Industrial and Energy

Driscoplex® Pipe Series	Features	Applicable Standards	Pipe Materials Designation & (Cell Classification)
1000 (IPS) (Industrial, International, various, etc.)	IPS (Iron Pipe Size) Black pipe is standard	ASTM D3035 ASTM F714	PE4710/3408 (445574C)
4100 FM (IPS) 4000 FM (DIPS)	IPS (Iron Pipe Size) DIPS (Ductile iron pipe size) Solid black, Black w/ red stripes Black w/ blue stripes	FMA Class Number 1613 AWWA C901, AWWA C906 ASTM D3035, ASTM F714	PE4710/3408 Meets and Exceeds (445574C - 345464C)
4100 (IPS) (Municipal & Industrial potable water, raw water, process water, various)	IPS (Iron Pipe Size) Black pipe is standard <u>Optional Color Striping Available:</u> Black w/ blue stripes Black w/ green Stripes Black w/ lavender stripes	ASTM F714 & ASTM D3035 AWWA C901 & AWWA C906 NSF 61	PE4710/3408 (445574C)
4000 (DIPS) (Municipal & Industrial potable water, raw water, process water, various)	DIPS (Ductile iron pipe size) 3 pair of equally spaced blue stripes is standard <u>Optional Color Striping Available:</u> Black w/ green Stripes Black w/ lavender stripes <u>Optional: Black Pipe: (No Stripe)</u>	ASTM F714 & ASTM D3035 AWWA C901 & AWWA C906 NSF 61	PE4710/3408 (445574C)
4600 (IPS) 4700 (DIPS) (Municipal & Industrial sewer, various, etc.)	IPS (Iron Pipe Size) DIPS (Ductile iron pipe size) Grey Pipe is standard <u>Optional Color Striping Available:</u> Grey pipe with green stripes	ASTM F714 & ASTM D3035 AWWA C901 & AWWA C906	PE4710/3408 (445574C)
5100 (IPS, CTS & SIDR) Potable water	Black pipe with blue or white print line	AWWA C901, NSF 14 ASTM D2737, ASTM D2239 or ASTM D3035	PE4710 (445574C)
5300 (IPS) (Geothermal)	Black pipe is standard	ASTM D3035	PE4710/3408 (445574C)
6400 Crude, brine, gas; (oil field, landfill, gas gathering, fracking, etc.)	IPS (Iron Pipe Size) Black pipe is standard	API 15LE ASTM D2513	PE4710/3408 (445574C)
1700 (Mining & industrial, DR striped applications)	IPS (Iron Pipe Size) Single color stripe to identify DR	ASTM D3035 ASTM F714	PE4710/3408 (445574C)
9200 (Customer spec liner)	OD size and tolerances are specified by customer	ASTM D3035 ASTM F714	PE4710 (445574C)