

DRISCOPEX[®] 5100 ULTRALINE[®] HDPE TUBING

DRISCOPEX[®] 5100 Series ULTRALINE[®] HDPE Water Service Tubing



Ultraline[®] HDPE Water Service Tubing is available to meet your needs in compliance with ASTM D2239, ASTM D2737 or ASTM D3035 product standard.

Produced from only the highest rated HDPE pipe material, DRISCOPEX[®] 5100 Series Tubing is manufactured from PE4710 resin as listed in PPI-TR4.

DRISCOPEX[®] HDPE Pipe Advantages:

- | | | |
|------------------|----------------------|----------------------|
| ✓ Durable | ✓ Fatigue Free | ✓ Chemical Resistant |
| ✓ Leak Tight | ✓ Impact Resistant | ✓ UV Protection |
| ✓ Excellent Flow | ✓ Trenchless Install | ✓ Flexibility |
| ✓ Low Surge | ✓ Bend Radius | ✓ Environmental |

Ultraline[®] HDPE Water Service Pipe and Tubing from Performance Pipe meets the requirements of:

- AWWA C901
- NSF/ANSI 61
- NSF /ANSI 14

When Performance Matters Rely on
Performance Pipe

DRISCOPLEX[®] 5100 Series ULTRALINE[®]

ASTM D2239 Inside Diameter Controlled HDPE Pipe (IPS/SIDR)

Nominal Size (inches)	Dimension Ratio	OD / ID (Inches)	Coil Length / Pallet Quantity	Weight (lbs/100 ft)	Pressure Rating (psi)
3/4"	7	1.074" / 0.824"	100'/1800' or 400'/4000'	16	250 psi
1"	7	1.367" / 1.049"	100'/1800' or 300'/2400'	25	250 psi
1-1/4"	7	1.798" / 1.380"	100'/1500' or 300'/2100'	43	250 psi
1-1/2"	7	2.098" / 1.610"	100'/1400' or 300'/1800'	59	250 psi
2"	7	2.692" / 2.067"	100'/1000' or 300'/2100'	97	250 psi

ASTM D2737 Outside Diameter Controlled HDPE Tubing (CTS)

Nominal Size (inches)	Dimension Ratio	OD / ID (Inches)	Coil Length / Pallet Quantity	Weight (lbs/100 ft)	Pressure Rating (psi)
3/4"	9	0.875" / 0.669"	100'/1800' or 500'/7500'	10	250 psi
1"	9	1.125" / 0.860"	100'/1600' or 300'/4200'	17	250 psi
1-1/4"	9	1.375" / 1.051"	100'/1400' or 300'/2400'	26	250 psi
1-1/2"	9	1.625" / 1.241"	100'/1300' or 300'/2400'	36	250 psi
2"	9	2.125" / 1.625"	100'/1300' or 300'/2700'	61	250 psi

ASTM D3035 Outside Diameter Controlled HDPE Pipe (IPS/SDR)

Nominal Size (inches)	Dimension Ratio	OD / ID (Inches)	Coil Length / Pallet Quantity	Weight (lbs/100 ft)	Pressure Class (psi)
3/4"	9	1.050" / 0.803"	150'/1800' or 500'/3500'	15	250 psi
1"	9	1.315" / 1.005"	150'/1800' or 500'/3000'	23	250 psi
1-1/4"	9	1.660" / 1.269"	150'/1500' or 500'/6000'	37	250 psi
1-1/2"	9	1.900" / 1.452"	250'/2500' or 500'/4000'	49	250 psi
2"	9	2.375" / 1.816"	150'/1800' or 500'/3500'	77	250 psi
3"	9	3.500" / 2.676"	250'/1750' or 1000'/2000'	166	250 psi

This product flyer is intended for reference purposes. It should not be used in place of the advice from a licensed Professional Engineer. Ultraline[®] Water Service Tubing Pressure Class is based on applications at temperatures up to and including 80°F. Contact your Performance Pipe representative for additional sizes, information and installation guidelines or visit www.performancepipe.com